



HT28 RTJ 0 HT28 RTJ PRO

Performance & Productivity

- Best horizontal outreach of 23,85m
- Homogenous and fluid working envelope
- Outstanding RT capacities

Safety & Comfort

- Safe loading/unloading at twilight thanks to Activ'Lighting System (PRO model)
- Unmatched comfort & smoothness in elevation thanks to a unique regulation system of boom movements
- Excellent rigid boom

Cost efficiency

- Haulotte Activ'Screen on board diagnostic system
- Haulotte Stop Emission System which automatically turns off & on the engine
- Easy access to all components
- Modular basket quick and easy to repair





TECHNICAL DATA

HT28 RTJ O
4WD-2WS

HT28 RTJ PRO
4WD-4WS

Working height	27.9 m	
Platform height	25.9 m	
Horizontal outreach	23.85 m	
Below ground reach	3 m	
Lift capacity	230 kg (2 persons)	
F x G Platform size	2.44 x 0.91	
A Length - stowed	13.05 m	
H Length - storage	9.8 m	
B Width	2.48 m	
C Height - stowed	2.85 m	
I Height - storage	2.98 m	
Vertical jib rotation	133° (-66°/+67°)	
Jib length	1.83 m	
Boom rotation angle	84.5° (+74.5°/-10°)	
Turntable rotation	360° continuous	
Tailswing	150 cm	
D Wheelbase	2.8 m	
E Ground clearance	48 cm	
Tilt	4 °	
Drive speed	0.5 - 5 km/h	
Gradeability	45 %	
Turning radius - outside	6,55 m	4.35 m
Tires - foam-filled	Solid RT cured on 1025x365 mm	
Engine	Kubota Tier 3 - 49,3kW & Kubota Tier 4f - 53 kW	
Weight	17 900 kg	18 100 kg

